



# 华为WCDMA/CDMA模块设备在 Android系统的内核驱动集成指导文档



Huawei Technologies Co., Ltd.

华为技术有限公司

All rights reserved

版权所有 侵权必究



HUAWEI

文档名称: 华为 WCDMA/CDMA 模块设在 Android 系统的内核驱动集成指导文档

文档密级: 秘密

## Revision record 修订记录

Date 日期	Revision Version 修订 版本	CR ID / Defect ID CR号	Section Number 修改 章节	Change Description 修改描述	Author 作者
2011-2-9	V1.0			初稿	方晓志 00110321
2011-5-3	V1.0.1			基于系统自带驱动进行修改，使能电源管理。	刘其峰 KF39449
2011-8-25	V1.2.1			加入MC509在Android下升级失败的解决方案	刘其峰 KF39449
2011-11-10	V1.2.3			根据USB协议规范，加入零包机制。针对usb1.1协议不添加零包，针对usb2.0协议及以上添加零包。以解决模块升级遇到零包法处理问题。增加部分为4.1.1小节的第5部分内容。	刘其峰 KF39449



HUAWEI

文档名称: 华为 WCDMA/CDMA 模块设在 Android 系统的内核驱动集成指导文档

文档密级: 秘密

# 华为WCDMA/CDMA模块设备在 Android系统的内核驱动集成指导文档

## Catalog 目 录

1	目的.....	4
2	范围.....	4
3	总体概述.....	4
3.1	Android系统的Linux内核支持华为模块设备的驱动架构 .....	4
4	Android系统的Linux内核驱动集成方案.....	5
4.1	Android内核的USB串口驱动集成步骤.....	5
4.1.1	USB串口驱动集成的修改内容 .....	5
4.1.2	USB串口驱动集成配置的操作步骤 .....	10
5	附录.....	15
5.1	确认系统中是否已经存在正确的USB串口驱动 .....	15
5.2	获取单板当前的端口映射情况信息 .....	16



HUAWEI

文档名称: 华为 WCDMA/CDMA 模块设在 Android 系统的内核驱动集成指导文档

文档密级: 秘密

## 1 目的

本文档主要是针对华为模块设备基于Android系统的内核驱动集成开发活动进行相关的指导说明。主要面向基于Android系统的产品开发商的驱动开发人员。

## 2 范围

本文档适用于:


- 1) 华为WCDMA/CDMA制式的模块设备。
- 2) Android 2.3(linux-2.6.35内核)及以上版本的Android系统。

## 3 总体概述

### 3.1 Android 系统的 Linux 内核支持华为模块设备的驱动架构

华为模块设备和Android系统主要通过USB接口进行数据通信。Android系统上的Linux内核需要根据华为模块设备上报的USB设备接口加载USB驱动，USB驱动正确加载后，华为模块才能正常工作。

Android系统中和支持华为模块设备相关的Linux内核驱动架构，如下图所示：



如上图所示，在Linux系统中的USB驱动架构中，跟华为模块设备相关的驱动模块是USB串口驱动模块。其中，

- **USB串口驱动:** USB的串口驱动，支持如modem端口，AT端口等；该驱动模块的代码(option.c)已经内置在Linux内核的源码中。

## 4 Android 系统的 Linux 内核驱动集成方案

### 4.1 Android 内核的 USB 串口驱动集成步骤

本集成方案涉及到的Linux内核源码文件是：

drivers/usb/serial/option.c

drivers/usb/serial/usb\_wwan.c

#### 4.1.1 USB 串口驱动集成的修改内容

1. 因linux-2.6.35以上的内核已经自带 selective suspend 电源管理特性，所以我们只需将电源管理的开关打开，USB串口驱动就将支持 selective suspend 电源管理。
2. 只需在/drivers/usb/serial/option.c 中的option\_probe() 函数内加入红框部分语句如



下所示:

```
if (serial->dev->descriptor.idVendor == HUAWEI_VENDOR_ID) {
    if (0 != (serial->dev->config->desc.bmAttributes & 0x20)){
        usb_enable_autosuspend(serial->dev);
    }
}
data = serial->private = kzalloc(sizeof(struct usb_wwan_intf_private), GFP_KERNEL);

if (!data)
    return -ENOMEM;
```

详文如下:

```
if (serial->dev->descriptor.idVendor == HUAWEI_VENDOR_ID) {

    if (0 != (serial->dev->config->desc.bmAttributes & 0x20)){

        usb_enable_autosuspend(serial->dev);

    }
}
```

即可支持selective suspend 特性。

3. 增加对reset\_resume函数的调用, 加入红框部分语句如下所示:

```
static struct usb_driver option_driver = {
    .name      = "option",
    .probe     = usb_serial_probe,
    .disconnect = usb_serial_disconnect,
#define CONFIG_PM
    .suspend   = usb_serial_suspend,
    .resume    = usb_serial_resume,
    .reset_resume = usb_serial_resume,
    .supports_autosuspend = 1,
```

4. 增加了对新PID的支持, 修改部分如下:

- a) 增加图示红框部分宏定义



```
#include "usb-wwan.h"

/* Function prototypes */
static int option_probe(struct usb_serial *serial,
                        const struct usb_device_id *id);
static int option_send_setup(struct usb_serial_port *port);
static void option_instat_callback(struct urb *urb);

#define HW_USB_DEVICE_AND_INTERFACE_INFO(vend, cl, sc, pr) \
    .match_flags = USB_DEVICE_ID_MATCH_INT_INFO \
    | USB_DEVICE_ID_MATCH_VENDOR, \
    .idVendor = (vend), \
    .bInterfaceClass = (cl), \
    .bInterfaceSubClass = (sc), \
    .bInterfaceProtocol = (pr)
```

- b) 在 static const struct usb\_device\_id option\_ids[ ] id列表中增加如下语句:

```
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0xff, 0xff) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x01) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x02) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x03) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x04) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x05) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x06) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0A) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0B) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0C) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0D) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0E) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x0F) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x10) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x12) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x13) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x14) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x15) },
```



```
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x16) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x31) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x32) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x33) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x34) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x35) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x36) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3A) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3B) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3C) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3D) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3E) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x3F) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x01, 0x46) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x01) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x02) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x03) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x04) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x05) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x06) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0A) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0B) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0C) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0D) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0E) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x0F) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x10) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x12) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x13) },
```



```
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x14) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x15) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x16) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x31) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x32) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x33) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x34) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x35) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x36) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3A) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3B) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3C) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3D) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3E) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x3F) },  
{ HW_USB_DEVICE_AND_INTERFACE_INFO(HUAWEI_VENDOR_ID, 0xff, 0x02, 0x46) },
```

## 5. 添加零包机制，以解决模块升级问题，修改文件为 drivers/usb/serial/usb\_wwan.c

5.1. 增加对bcdUSB值的定义： #define HW\_bcdUSB 0x0110，增加对华为vid值的定义： #define HUAWEI\_VENDOR\_ID 0x12d1，如红框位置所示：

```
#include <linux/usb/serial.h>  
#include "usb-wwan.h"  
  
static int debug;  
#define HW_bcdUSB 0x0110  
#define HUAWEI_VENDOR_ID 0x12d1  
  
void usb_wwan_dtr_rts(struct usb_serial_port *port, int on)
```

5.2. 先在usb\_wwan\_write函数内增加定义： struct usb\_host\_endpoint \*ep；

然后在usb\_wwan\_write函数增加对零包的判断，增加部分如红框所示：



```
/* send the data */
memcpy(this_urb->transfer_buffer, buf, todo);
this_urb->transfer_buffer_length = todo;

if ((HUAWEI_VENDOR_ID == port->serial->dev->descriptor.idVendor)
    && (HW_bcdUSB != port->serial->dev->descriptor.bcdUSB)) {
    ep = usb_pipe_endpoint(this_urb->dev, this_urb->pipe);
    if (ep && (0 != this_urb->transfer_buffer_length)
        && (0 == this_urb->transfer_buffer_length % ep->desc.wMaxPacketSize)) {
        this_urb->transfer_flags |= URB_ZERO_PACKET;
    }
}
```

```
spin_lock_irqsave(&intfdata->susp_lock, flags);
```

6. 修改Android内核的编译配置(在kernel根目录下的.config文件中),确保下面的的配置项已经被选定。具体的配置操作请参考4.1.2节。

- i. USB电源管理特性的相关配置项:

```
CONFIG_USB_SUSPEND=y
```

- ii. USB串口驱动相关的配置项:

```
CONFIG_USB_SERIAL=y
```

```
CONFIG_USB_SERIAL_OPTION=y
```

```
CONFIG_USB_SERIAL_WWAN=y
```

- iii. PPP拨号的相关配置项:

```
CONFIG_PPP=y
```

```
CONFIG_PPP_MULTILINK=y
```

```
CONFIG_PPP_FILTER=y
```

```
CONFIG_PPP_ASYNC=y
```


```
CONFIG_PPP_SYNC_TTY=y
```

```
CONFIG_PPP_DEFLATE=y
```

```
CONFIG_PPP BSDCOMP=y
```



#### 4.1.2 USB 串口驱动集成配置的操作步骤




1. 打开Terminal工具, 进入kernel目录(假定kernel在/usr/src/mydroid/目录下, 即cd /usr/src/mydroid/kernel), 然后执行make <configuration>命令(在本文中, 假定使用标准的make menuconfig)。



## 2. 选择相关的配置项

### 1. USB电源管理特性的相关配置项:







## 2. USB串口驱动相关的配置项

```
Linux Kernel Configuration
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable

General setup --->
[*] Enable loadable module support --->
[*] Enable the block layer --->
System Type --->
Bus support --->
Kernel Features --->
Boot options --->
CPU Power Management --->
Floating point emulation --->
Userspace binary formats --->
Power management options --->
[*] Networking support --->
Device Drivers ---> |
File systems --->
Kernel hacking --->
Security options --->
< > Cryptographic API --->
Library routines --->
--->
Load an Alternate Configuration File
v( +) <Select> < Exit > < Help >

Device Drivers
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable

^(-)
Character devices --->
<*> I2C support --->
[*] SPI support --->
PPS support --->
-* GPIO Support --->
< > Dallas's 1-wire support --->
<*> Power supply class support --->
< > Hardware Monitoring support --->
< > Generic Thermal sysfs driver --->
[ ] Watchdog Timer Support --->
Sonics Silicon Backplane --->
Multifunction device drivers --->
[*] Voltage and Current Regulator Support ---> ↵
<*> Multimedia support --->
Graphics support --->
< > Sound card support --->
[*] HID Devices --->
[*] USB support --->
< > Ultra Wideband devices (EXPERIMENTAL) --->
<*> MMC/SD/SDIO card support --->
v( +) <Select> < Exit > < Help >

USB support
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable

^(-)
< > Olympus MAUSB-10/Fuji DPC-R1 support
< > Support OneTouch Button on Maxtor Hard Drives
< > Support for Rio Karma music player
< > SAT emulation on Cypress USB/ATA Bridge with ATACB
[ ] The shared table of common (or usual) storage devices
*** USB Imaging devices ***
< > USB Mustek MDC800 Digital Camera support
< > Microtek X6USB scanner support
*** USB port drivers ***
< > USB Serial Converter support --->
*** USB Miscellaneous drivers ***
< > EMI 6|2m USB Audio interface support
< > EMI 2|6 USB Audio interface support
< > ADU devices from Ontral Control Systems ↵
< > USB 7-Segment LED Display
< > USB Diamond Rio500 support
< > USB Lego Infrared Tower support
< > USB LCD driver support
< > USB BlackBerry recharge support
< > USB LED driver support
v( +) <Select> < Exit > < Help >
```



```
USB Serial Converter support
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable
^(-)
< > USB Moschip 7720 Serial Driver (NEW)
< > USB Moschip 7840/7820 USB Serial Driver (NEW)
< > USB Motorola Phone modem driver (NEW)
< > USB Navman GPS device (NEW)
< > USB Prolific 2303 Single Port Serial Driver (NEW)
< > USB Ours Technology Inc. OTi-6858 USB To RS232 Bridge Controller (NEW)
< > USB Qualcomm Serial modem (NEW)
< > USB SPCP8x5 USB To Serial Driver (NEW)
< > USB HP4x Calculators support (NEW)
< > USB Safe Serial (Encapsulated) Driver (NEW)
< > USB Siemens MPI driver (NEW)
< > USB Sierra Wireless Driver (NEW)
< > USB Symbol Barcode driver (serial mode) (NEW)
< > USB TI 3410/5052 Serial Driver (NEW)
< > USB REINER SCT cyberJack pinpad/e-com chipcard reader (NEW)
< > USB Xircom / Entrega Single Port Serial Driver (NEW)
[*] USB driver for GSM and CDMA modems
< > USB ZYXEL omni.net LCD Plus Driver (NEW)
< > USB Opticon Barcode driver (serial mode) (NEW)
< > USB Debugging Device (NEW)

<Select> < Exit > < Help >
```


### 3. PPP拨号的相关配置项

```
Linux Kernel Configuration
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable
General setup --->
[*] Enable loadable module support --->
[*] Enable the block layer --->
System Type --->
Bus support --->
Kernel Features --->
Boot options --->
CPU Power Management --->
Floating point emulation --->
Userspace binary formats --->
Power management options --->
[*] Networking support --->
[*] Device Drivers --->
File systems --->
Kernel hacking --->
Security options --->
< > Cryptographic API --->
Library routines --->
--->
Load an Alternate Configuration File ↵
v( +)


<Select> < Exit > < Help >
```

```
Device Drivers
Arrow keys navigate the menu. <Enter> selects submenus --->. Highlighted letters are hotkeys. Pressing
<Y> includes, <N> excludes, <M> modularizes features. Press <Esc><Esc> to exit, <?> for Help, </> for
Search. Legend: [*] built-in [ ] excluded <M> module < > module capable
^(-)
< > Parallel port support --->
[ ] Block devices --->
[*] Misc devices --->
< > ATA/ATAPI/MFM/RLL support --->
SCSI device support --->
< > Serial ATA (prod) and Parallel ATA (experimental) drivers --->
[ ] Multiple devices driver support (RAID and LVM) --->
[ ] Fusion MPT device support --->
IEEE 1394 (FireWire) support --->
< > I2O device support --->
[*] Network device support --->
[ ] ISDN support --->
< > Telephony support --->
Input device support --->
Character devices --->
<*> I2C support --->
[*] SPI support --->
PPS support --->
-*. GPIO Support --->
< > Dallas's 1-wire support --->
v( +)

<Select> < Exit > < Help >
```



7. 如上操作选完所须选项后，通过选择<Exit>按钮，逐层退出各个配置界面。最后在保存配置界面中，选择”Yes”选项并退出。



8. 完成配置后，即可运行 make 命令，开始编译修改后的内核。

## 5 附录

### 5.1 确认系统中是否已经存在正确的 USB 串口驱动

执行如下命令查看内核的log信息：

```
dmesg
```

假如内核的log信息中存在如下(或相似)的信息，则说明系统已经存在正确的USB串口驱动了：



```
[ 1.765889] usb usb1: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 1.755893] usb usb1: Product: EHCI Host Controller
[ 1.755897] usb usb1: Manufacturer: Linux 2.6.36.3 ehci_hcd
[ 1.755900] usb usb1: SerialNumber: 0000:00:1a.0
[ 1.755944] hub 1-0:1.0: USB hub found
[ 1.755983] hub 1-0:1.0: 3 ports detected
[ 1.756049] ehci_hcd 0000:00:1d.0: PCI INT A -> GSI 23 (level, low) -> IRQ 23
[ 1.756061] ehci_hcd 0000:00:1d.0: EHCI Host Controller
[ 1.756066] ehci_hcd 0000:00:1d.0: new USB bus registered, assigned bus number 2
[ 1.756085] ehci_hcd 0000:00:1d.0: debug port 2
[ 1.760048] ehci_hcd 0000:00:1d.0: irq 23, io mem 0xfe526000
[ 1.769818] ehci_hcd 0000:00:1d.0: USB 2.0 started, EHCI 1.00
[ 1.769854] usb usb2: New USB device found, idVendor=1d6b, idProduct=0002
[ 1.769858] usb usb2: New USB device strings: Mfr=3, Product=2, SerialNumber=1
[ 1.769862] usb usb2: Product: EHCI Host Controller
[ 1.769866] usb usb2: Manufacturer: Linux 2.6.36.3 ehci_hcd
[ 1.769869] usb usb2: SerialNumber: 0000:00:1d.0
[ 1.769951] hub 2-0:1.0: USB hub found
[ 1.769953] hub 2-0:1.0: 3 ports detected
[ 1.770011] usbcore: registered new interface driver usbserial
[ 1.770018] USB Serial support registered for generic
[ 1.770025] usbcore: registered new interface driver usbserial_generic
[ 1.770026] usbserial: USB Serial Driver core
[ 1.770032] USB Serial support registered for GSM modem (1-port)
[ 1.770044] usbcore: registered new interface driver option
```

## 5.2 获取单板当前的端口映射情况信息

- 查看驱动是否加载成功，同样执行 dmesg 命令，假如log信息中存在如下(或相似)的信息，则说明驱动已经被成功加载，(idProduct因产品的不同而不同)。

```
[276504.796530] usb 2-1.4: new high speed USB device using ehci_hcd and address 6
[276504.883808] usb 2-1.4: New USB device found, idVendor=12d1, idProduct=1404
[276504.883812] usb 2-1.4: New USB device strings: Mfr=3, Product=2, SerialNumber=0
[276504.883816] usb 2-1.4: Product: HUAWEI MOBILE WCDMA EM770W
[276504.883819] usb 2-1.4: Manufacturer: HUAWEI Technology
[276504.978546] USB Serial support registered for GSM modem (1-port)
[276504.978717] option 2-1.4:1.0: GSM modem (1-port) converter detected
[276504.978970] usb 2-1.4: GSM modem (1-port) converter now attached to ttyUSB0
[276504.978987] option 2-1.4:1.1: GSM modem (1-port) converter detected
[276504.979085] usb 2-1.4: GSM modem (1-port) converter now attached to ttyUSB1
[276504.979100] option 2-1.4:1.2: GSM modem (1-port) converter detected
[276504.979162] usb 2-1.4: GSM modem (1-port) converter now attached to ttyUSB2
[276504.979175] option 2-1.4:1.3: GSM modem (1-port) converter detected
[276504.979234] usb 2-1.4: GSM modem (1-port) converter now attached to ttyUSB3
[276504.979248] option 2-1.4:1.4: GSM modem (1-port) converter detected
[276504.979312] usb 2-1.4: GSM modem (1-port) converter now attached to ttyUSB4
```

- 当前模块设备的modem、pcui等端口的设备文件名称 查询命令：

```
ls /dev/ttyUSB*
```

```
# ls /dev/ttyU*
/dev/ttyUSB0
/dev/ttyUSB1
/dev/ttyUSB2 node_id [ETH_ALEN]
/dev/ttyUSB3
/dev/ttyUSB4 driverName [] = 0x00000000
#
```