


IRRIGATION LEGEND

SYMBOL	MFG.	MODEL NUMBER	DESCRIPTION	GPM
	RAINBIRD	RWS-M-B-C-P-1402, 2 PER TREE	ROOT WATERING SYSTEM	2 X .5 = 1.0
	RAINBIRD	ESF-LXMEF-12 STATIONS	AUTOMATIC CONTROLLER - INSTALL ON STEEL ENCLOSURE OR APPROVED EQUAL	
	NETAFIM	DF150S-140 1-1/2" FILTER OR APPROVED EQUAL	MANUAL DISC WATER FILTER w/ 140 FIL BALL VALVE LINE SIZED	
	WATTS	WBV STD PORT THD BRASS RAIN CHECK	AUTOMATIC RAIN SHUT OFF DEVICE - INC RECS. LOCATION TO BE APPROVED BY ?	
	RAINBIRD	33D-LRC	QUICK COUPLER - INSTALL IN GREEN FLUX BOX CARSON OR APRVD EQUAL O.C.S	
	RAINBIRD	FR5B-FRS-D SERIES	AUTOMATIC REMOTE CONTROL VALVE - ANTI-SIPHON AUTOMATIC CONTROL ZONE	
	RAINBIRD	XACZ-.75 & 1.0 - COM - FR5	AUTOMATIC CONTROL ZONE KIT	
	RAINBIRD	XCZ-.75 & 1.0 - COM - FR5	AUTOMATIC REMOTE CONTROL VALVE - OPERATION INDICATOR	
	IRBITROL	MASTER VALVE: MODEL 102P2	FLUSH VALVE	
	NETAFIM	# 10 - F - 01	REDUCED PRESSURE BACKFLOW PREVENTER TO BE TAGGED CERTIFIED - INSTALL IN RESISTANT LANDSCAPE GREEN FMCLC	
	NETAFIM	TLOSQMFV-1	FLUSH VALVE	
	FEBCO	B25 Y LINE SIZE	FLUSH VALVE	
	RAINBIRD	1/2" & 3/4" SUBSURFACE DRIFTLINE @ 1'-16" O.C.	LANDSCAPE DRIFTLINE @ 1'-16" O.C.	6 GPM / Emitter
	LATERAL LINE	SCH. 40 PVC SIZE AS NOTED - 1/2" MINIMUM COVER		
	MAIN LINE	CLASS 315 PVC 2" AND LARGER SCH 40 PVC 1-1/2" AND SMALLER		
	SLEEVE	SIZE AS NOTED - 24" MINIMUM COVER		
	ELECTRICAL CONTROL WIRE SLEEVE	SCH. 40 PVC SIZE = TWICE DIAMETER OF PIPE - 24" MINIMUM COVER		
	WATER METER	24" COVER MIN., SIZE AS NECESSARY		
	P.O.C.	PRIVATE WATER METER		
	COMMON 1-1/2" WATER METER			



NOTES: LANDSCAPE CONTRACTOR SHALL INSTALL A PRESSURE REGULATOR WHEN PRESSURE EXCEEDS 80 P.S.I.

CHECK VALVES AND/OR SWING CHECK VALVES ARE REQUIRED ON AND OTHER AREAS TO PREVENT LOW HEAD DRAINAGE. INSTALL AS INSTALLED A MIN. OF 1 AIR RELIEF VALVE A 1 FLUSH VALVE ON EACH